



中山市晶艺光电科技有限公司
ZHONGSHAN JEWELLY OPTOELECTRONIC TECHNOLOGY CO.,LTD.

样品承认书

品名：一位数码管 0.36"共阴红色

规格：ULS-3162AS26

编号：2017-07

客户签字栏		
核准	审核	承认

本公司签字栏		
核准	审核	制作

地址：广东省中山市南区昌盛路 4 号

电话：0760-23886633 23886636 23886632

传真：0760-23886658

网址：www.jlul.com

电子邮箱：jinglei@jlul.com



ELECTRICAL AND OPTICAL CHARACTERISTICS (Ta=25°C)

Remark: Viewing angle is the Off-axis angle at which the luminous intensity is half the axial luminous intensity.

Reverse Voltage.....5V


Reverse Current($V_R=5V$).....20 μA

Operating Temperature Range.....-25°C~+100°C

Storage Temperature Range.....-30℃~+100℃

Lead Soldering Temperature..... 260°C For 5 Seconds

PACKAGE DIMENSION:



客户名称:

工程确认:

日期:



中山市晶艺光电科技有限公司

ZHONGSHAN JEWELRY OPTOELECTRONIC TECHNOLOGY CO.,LTD.

PART NO.: ULS-3162AS26

TYPICAL ELECTRO-OPTICAL CHARACTERISTICS CURVE:

